

PATENT APPLICATION
BIOPSY LOCALIZATION METHOD AND DEVICE

Inventor(s):

Richard Eustis Fulton III
1556 Wellington Avenue
Grand Junction, Colorado 81501,
a citizen of United States of America

William R. Dubrul
1 Uccelli Blvd., Suite A-7
Redwood City, California 94063,
a citizen of United States of America

Entity: Small

BIOPSY LOCALIZATION METHOD AND DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of the following Provisional patent applications. Biopsy Localization Device, Application No. 60/090,243, filed June 22, 1998; Biopsy Localization and Hemostasis Device, Application No. 60/092,734, filed July 14, 1998; Device and Method of Biopsy Localization and Hemostasis, Application No. 60/114,863, filed January 6, 1999; and Device and Method of Biopsy Localization, Hemostasis & Cancer Therapy, Application No. 60/117,421, filed January 25, 1999.

BACKGROUND OF THE INVENTION

In the U.S. alone approximately one million women will have breast biopsies because of irregular mammograms and palpable abnormalities. See Fig. 1 which diagrams the current treatment algorithm for non-palpable breast lesions. Biopsies can be done in a number of different ways for non-palpable lesions, including surgical excisional biopsies and stereotactic and ultrasound guided needle breast biopsies. In the case of image directed biopsy, the radiologist or other physician takes a small sample of the irregular tissue for laboratory analysis. If the biopsy proves to be malignant, additional surgery (typically a lumpectomy or a mastectomy) is required. The patient then returns to the radiologist a day or two later where the biopsy site (the site of the lesion) is relocated by method called needle localization, a preoperative localization in preparation for the surgery.

Locating the previously biopsied area after surgical excision type of biopsy is usually not a problem because of the deformity caused by the surgery. However, if the biopsy had been done with an image directed needle technique, as is common, help in relocating the biopsy site is usually needed. One procedure to permit the biopsy site to be relocated by the radiologist during preoperative localization is to leave some of the suspicious calcifications; this has its drawbacks.

Another way to help the radiologist relocate the biopsy site involves the use of a small metallic surgical clip, such as those made by Biopsys. The metallic clip can be deployed through the biopsy needle, and is left at the biopsy site at the time of the original biopsy. With the metallic clip as a guide, the radiologist typically inserts a barbed or hooked wire, such as the Hawkins, Kopans, Homer, Sadowski, and other needles, back

into the patient's breast and positions the tip of the wire at the biopsy site using mammography to document the placement. The patient is then taken to the operating room with the needle apparatus sticking out of the patient's breast. While the clip provides a good indication of the biopsy site to the radiologist during preoperative localization, the clip remains permanently within the 80% of patients with benign diagnoses. Also, because the clip is necessarily attached to a single position at the periphery of the biopsy site, rather than the center of the biopsy site, its location may provide a misleading indication of the location of diseased tissue during any subsequent medical intervention. In addition, the soft nature of breast tissue permits the tip of the barbed or hooked needle to be relatively easily dislodged from the biopsy site. The clip is also relatively expensive.

Another localization method involves the use of laser light from the tip of an optical fiber connected to a laser. A pair of hooks at the tip of the optical fiber secures the tip at the biopsy site; the glow indicates the position of the tip through several centimeters of breast tissue. This procedure suffers from some of the same problems associated with the use of barbed or hooked wires. Another preoperative localization procedure injects medical-grade powdered carbon suspension from the lesion to the skin surface. This procedure also has certain problems, including the creation of discontinuities along the carbon trail.

SUMMARY OF THE INVENTION

The present invention is directed to a biopsy localization method and device which uses a locatable bioabsorbable element left at the biopsy site so that if testing of the biopsy sample indicates a need to do so, the biopsy site can be relocated by finding the bioabsorbable element. This eliminates the need to use of metallic clips during biopsies and often eliminates the need for a return to the radiologist for pre-operative needle localization. In addition, the bioabsorbable element can be used as a therapeutic tool for treatment of the diseased lesion and for hemostasis.

A biopsy localization device made according to the invention includes a bioabsorbable element delivered in a pre-delivery state to a soft tissue biopsy site of a patient by an element delivery device. The bioabsorbable element may be palpably harder than the surrounding soft tissue at the biopsy site when in the post-delivery state.

One preferred material used as the bioabsorbable element is a dehydrated collagen plug. This type of plug may swell and is palpable for subsequent location by the

surgeon. The collagen plug may not swell at all. In some situations, such as with small breasted women or where the biopsy site is close to the surface, a non-swellable bioabsorbable material, such as a round pellet of PGA, can be used instead of a swellable bioabsorbable material. The bioabsorbable material can also be made so that it is absorbed quickly to produce a local tissue inflammation; such a localized inflammation can be used to locate the biopsy site instead of location by palpation. Instead of leaving, for example, a collagen plug, a PGA pellet or a bioabsorbable suture material at the biopsy site for location by palpation or inflammation, a length of bioabsorbable suture material, a collagen filament, or other bioabsorbable material extending from the biopsy site out through the skin can be used. In this case the surgeon can follow the bioabsorbable suture material to the biopsy site in a manner similar to that used with Hawkins needles. In other cases, such as in the case of a deeply located lesion or large breast, the bioabsorbable material may need to be located by the radiologist, by for example, ultrasound or mammography. In any event the bioabsorbable material will typically be absorbed within about a month of placement. The invention thus eliminates the use of metal clips during biopsies and usually eliminates the need for return to the radiologist for preoperative localization.

While the primary use of the device is intended to localize the site of needle biopsies for possible future surgical excision, the device may also be useful in marking the site of surgical excisional biopsies. For example, during a wide surgical excision for cancer diagnosed by a recent surgical excisional biopsy, surgeons frequently have difficulty in determining the precise relationship of the previously excised tissue to the surgical wound. Therefore, more tissue is removed than might have been removed had the exact location of the previous lesion been more definite. With the present invention, a bioabsorbable element may be inserted into the biopsy site during a surgical excisional biopsy before the wound is closed to mark the site for potential wide excision should the biopsy reveal cancer. Alternatively, a bioabsorbable element may be placed at the biopsy site using a delivery device by partially or completely closing the wound and then depositing the bioabsorbable element through the delivery device and removing the delivery device through the closed incision. The presence of the palpable marker within the previous excisional biopsy site would allow the surgeon to more easily and confidently remove tissue around this site, and preserve more normal breast tissue.

Another use of the device is to primarily localize a non-palpable lesion prior to surgical excisional biopsy. Instead of using the needle/wire apparatus which has

0995878-11001
CONFIDENTIAL
a tendency to migrate and become dislodged with traction, the palpable marker may be inserted into the suspicious area of the breast under mammographic or ultrasonic guidance immediately prior to the surgical excisional biopsy. This would provide a palpable locator for the surgeon as described above. In this instance, the marker would
5 only need to be palpable, and not necessarily bioresorbable, since the intent would be to remove it in all cases.

In addition to permitting the biopsy site to be located by subsequent palpation or other means, the invention also can provide hemostasis and therapeutic benefits. Since the bioabsorbability can be varied from a day or two to a year or more,
10 the material may be used to treat the diseased tissue and not just locate it. Some current therapies include radiation, chemotherapy, gene therapy as well as other technologies and therapies. Because the bioabsorbability can be easily varied, a medium can be placed into the bioabsorbable element and be externally excited or triggered in those cases where the biopsy results are malignant. Further, the bioabsorbability concept can be used for future
15 implantation of a therapeutic agent. For example, if the bioabsorbable element is a dehydrated collagen, this material could be used as a reservoir for, for example, delivery of materials that effect chemotherapy, brachytherapy, etc. Once the laboratory results are received and show the biopsy is malignant and therapy is required, by surgical excision or otherwise, the physician may inject, for example, a radiation pellet, a chemotherapeutic
20 agent or a gene therapeutic agent into or adjacent to the bioabsorbable element for direct treatment of the diseased tissue.

The change in the bioabsorbable element can be via one of several ways, such as hydration or desiccation, change in temperature, electrical stimulation, magnetic stimulation, chemical or physical reaction with another material, additives, enzymatic
25 reactions, ionization, electrical charges, absorption, as well as other means. The invention may employ one or more of these techniques or measures or others, to change the consistency, hardness and or size of the bioabsorbable element between its deployed and non-deployed states. The visual detectability of the bioabsorbable element may be aided by the use of a coloring agent, such as methylene blue or some other dye. The
30 radiographic detectability of the element may be enhanced by a radiopaque marker. As well, ultrasonic detectability may be enhanced by special treatment of the bioresorbable element.

The bioresorbable element may have margins which are roughened so as to prevent migration within the tissues. Filaments extending from the margins of the

bioresorbable element may be utilized also to stabilize the position of the device within the cavity. The filaments may or may not be composed of the same material as the bioresorbable element.

The provision of hemostasis helps to lessen the bleeding and swelling within and about the biopsy site. This can be accomplished by physical or chemical means. That is, the device may swell so that it essentially fills the biopsy cavity or the device may have a chemical reaction with blood or blood products to cause effective blood clotting, or both. Other methods for causing local hemostasis are also possible with the invention.

Other features and advantages of the invention will appear from the following description in which the preferred embodiments and methods have been set forth in detail in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a flow diagram of a conventional treatment algorithm for non-palpable breast lesions;

Fig. 2 is a flow diagram of a treatment algorithm according to the present invention;

Fig. 3 is a simplified view illustrating a biopsy needle assembly obtaining a tissue sample of an abnormality at a target site;

Fig. 4 illustrates the main housing and sheath of the needle biopsy assembly left in place after the tissue sample has been removed leaving a biopsied open region at the target site;

Fig. 5 illustrates the barrel of the delivery device of Fig. 4 inserted into the main housing of the biopsy needle assembly and the plunger depressed injecting the bioabsorbable element into the biopsied open region, thus effectively filling the biopsied open region at the target site;

Fig. 6 illustrates the location of the bioabsorbable element of Fig. 5 with the surgeon using his or her fingers; and

Fig. 7 illustrates a bioabsorbable thread extending from the bioabsorbable element of Fig. 5 up through the patient's skin, the thread being delivered to the bioabsorbable element using the delivery device of Figs. 4 and 5.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Fig. 2 illustrates a treatment algorithm 2 according to the present invention. As a result of a routine mammography 4, a tumor or other abnormality may be detected as at 6. The typical response will often include additional magnification

5 mammograms or a follow-up mammogram scheduled for some time in the future, such as six months. This is indicated at 8. If the tumor is not palpable, see 9, an image guided needle biopsy by a breast radiologist is typically conducted as at 10. Image guided needle biopsies can be done in a number of ways. Presently, stereotactic (x-ray) and ultrasound

10 and minimal trauma to the patient. Stereotactic needle biopsies typically use a stereotactic table, such as made by Fisher or Lorad, which provides mammography (x-ray) guidance to a biopsy needle assembly. Ultrasound guided biopsies can be conducted with any one of a number of commercially available instruments. An exemplary biopsy needle assembly 14, illustrated in Fig. 3, includes a biopsy needle 13 passing through a

15 sheath 20 extending from a hollow main housing 22. The tip 12 of biopsy needle 13 of biopsy needle assembly 14 is automatically inserted to the abnormality 16 at the target site 18. Biopsy needle 13 has a laterally directed side opening 24 adjacent to tip 12 used to capture a tissue sample of abnormality 16. Once the tissue samples have been obtained, the removed tissue creates a biopsied open region 26 at target site 18. See Fig.

20 4. Following the removal of biopsy needle 13 from sheath 20 and main housing 22, the barrel 30 of a bioabsorbable element delivery device 32 is inserted through main housing 22 and into sheath 20. Barrel 30 contains a bioabsorbable element 34, see Fig. 5 Bioabsorbable element 34 is, in this preferred embodiment, a plug of dehydrated collagen, such as that sold by several companies such as Davol, Datascope, Integra Life

25 Sciences, Collagen Matrix, Vascular Solutions, et al. Bioabsorbable element 34 may swell on contact with an aqueous liquid within biopsied open region 26 and substantially fills the biopsied open region as suggested in Fig. 5. In this preferred embodiment, bioabsorbable element 34 is transformed from its pre-delivery state within barrel 30 to its post-delivery state at region 26 and in the process swells and becomes somewhat softer in

30 its post-delivery state than in its pre-delivery state. However, in its post-delivery state, bioabsorbable element 34 is palpably harder, preferably at least about 1.5 times harder, than the surrounding soft tissue, typically breast tissue 36. This permits bioabsorbable element 34 at the target site 18 to be relocated by palpation of the patient by the

physician, see Fig. 6, to find the bioabsorbable element 6 and as discussed in more detail below.

A bioabsorbable element could be made of materials other than collagen and could be in a form other than a solid, relatively hard plug in its pre-delivery state. For example, bioabsorbable element 34 in its pre-delivery state within barrel 30 could be in a liquid or otherwise flowable form; after being deposited at open region 26 at target site 18, the bioabsorbable element could change to become palpably harder than the surrounding tissue 36 to permit subsequent relocation of target site 18 by palpation. In some situations, it may be desired that bioabsorbable element 34 not change its size or hardness between its pre-delivery state and its post-delivery state, such as being palpably harder than the surrounding tissue 36 in both states. In a preferred embodiment, transformation of bioabsorbable element 34 is by contact with an aqueous liquid. However, transformation of the bioabsorbable element, which can be in terms of, for example, hardness, texture, shape, size, or a combination thereof, can be due to other factors, such as application of thermal energy, radiation, magnetic energy, etc.

Returning again to Fig. 2, it is seen that after insertion of bioabsorbable element 34, the biopsy sample is sent to pathology for evaluation at 36. If the pathology report, which is available a day or two after the biopsy, is benign, the patient is so informed and the bioabsorbable element simply is absorbed by the patient within, for example, a month as at 38. If the pathology report is positive, so that cancer is found, the biopsied open region 26 at the target site 18 is located by the surgeon by palpation as suggested by Fig. 6. After finding the target site by palpation, which eliminates the need for preoperative localization by the radiologist, appropriate medical treatment, such as excisional surgery, can be performed.

If the tumor is palpable, the surgeon may choose to make a direct incisional biopsy as at 48. According to the present invention, bioabsorbable delivery device 32 could be used to place bioabsorbable element 34 at the site of the incisional biopsy. After removal of delivery device 32, the incision would be closed, the biopsy sample would be sent to pathology and the patient would go home with the procedure preceding as discussed above, starting with item 36.

It may be preferred that bioabsorbable element 34 also act as a hemostatic agent to stop bleeding at site 18 by virtue of physical means, by filling or substantially filling open region 26, as well as chemical means through the chemical interaction, such as coagulation, with blood components. In addition, bioabsorbable element 34 could be

contact with an aqueous liquid. It is preferred that the bioabsorbable element has a longest dimension of at least about 0.5cm in its post-delivery state to aid its location by palpation.

While the bioabsorbable element is preferably made of collagen in one embodiment, the bioabsorbable element can include, for example, one or more of the following materials; polyactic and polyglycolic acids, polyorthoesters, resorbable silicones and urethanes, lipids, polysaccharides, starches, ceramics, polyamino acids, proteins, hydrogels and other gels, gelatins, polymers, cellulose, elastin, and the like.

In some situations it may be desired to use a bioabsorbable filament 44 extending from bioabsorbable element 34 through the patient's skin 46 as shown in Fig. 7. This can be accomplished by delivering bioabsorbable filament 44 through sheath 20 as bioabsorbable element 34 is injected into region 26 at target site 18. In some situations it may not be possible or desirable to use bioabsorbable element 34; in those situations it may be useful to provide for only bioabsorbable filament 44 extending from target site 18 to above the patient's skin 46.

While it is presently preferred that bioabsorbable element delivery device 32 be guided through a portion of needle assembly 14, that is sheath 20 and main housing 22, in some situations it may be useful to cover sheath 20 with an outer sheath which would be left in place after the biopsy sample has been removed and the entire biopsy needle assembly 14 has been removed. The sheath left in place would then be used to guide barrel 30 of delivery device 32 to target site 18. Of course, delivery device 32 could take a number of different forms such as a syringe containing fluid or paste that is injected through a needle or through the housing 22 and sheath 20 or through an outer sheath. Alternatively, other delivery devices could be employed for delivery of bioresorbable element 34.

The invention has applicability toward the correction of a defect that is caused by breast tissue removal for biopsy or diseased tissue removal. Collagen is often placed in the body where it is eventually replaced by human autogenous tissue. Hence, the invention could be used for the repair of tissue that has been damaged due to tissue removal. The delivery device described heretofore could be used for installing a material (synthetic or mammalian) into the cavity for such a cosmetic or reconstructive repair. The material would typically be an effectively non-bioabsorbable material, such as a silicon gel-filled capsule or bag.

THE UNIVERSITY OF CHICAGO

22.